

FAN-Evaluator / Stainless Steel (FAN-E/SS) – Commercial CIRCULAR CONFIGURATION 90° FLANGE



STANDARD CONSTRUCTION

Casing.	Up to 45" dia: 18 ga. type 316 stainless steel, continuously welded casing seams. Over 45" dia: 14 ga. type 316 stainless steel, continuously welded casing seams.
Flanges.	Up to 24" dia: 1" flange, 14 ga. type 316 stainless steel, fusion welded to casing. 25" to 44" dia: 1-1/2" flange, 14 ga. type 316 stainless steel, fusion welded to casing. 45" plus: 2" flange, 3/16" barstock, type 316 stainless steel, fusion welded to casing.
Air Equalizer/Straightener.	1/2" cell, 3" deep, 2 mil thick, type 304SS, bonded construction, rated to 4000 FPM and 350°F.
Total Pressure Header.	Type 316 stainless steel tubing, welded construction.
Static Pressure Header.	Type 316 stainless steel tubing, welded construction.
Operating Temperature.	Continuous operation to 350°F.
Connection Fittings.	1/4" stainless steel compression type.

OPTIONAL CONSTRUCTION

<p>Casing</p> <p><input type="checkbox"/> 10 ga. type 316SS, continuously welded seam</p> <p>Connection Fittings</p> <p><input type="checkbox"/> Seal welded fittings</p> <p>Engraved Identification Tags</p> <p><input type="checkbox"/> Stainless Steel</p> <p><input type="checkbox"/> Plastic</p>	<p>Flanges</p> <p><input type="checkbox"/> 10 ga. 316SS, fusion welded</p> <p><input type="checkbox"/> Extended Flange Size: _____</p> <p>Bolt Holes</p> <p>Qty Per Flange: _____ Hole Size: _____</p> <p>Bolt Circle Diameter: _____</p>
--	---

DIMENSIONAL SPECIFICATIONS

