

LO-flo PITOT TRAVERSE STATION ALUMINUM

STANDARD CONSTRUCTION

<p>Casing. Flanges. Air Equalizer and Straightener. Total Pressure Header. Static Pressure Probe. Casing Depth. Connection Fittings. Operating Temperature.</p>	<p>Type 3004-H26 aluminum tube. 1" flange, 0.08" aluminum sheetmetal, fusion welded to the casing. Corrosion resistant 3003 aluminum. 3" deep x 3/8" cell. Copper tubing assembled with 50/50 tin/lead solder. Stainless steel mounting bracket. Copper tubing with 50/50 tin/lead solder. 8" deep on flanged unit. 10" deep on non-flanged unit. 1/4" brass compression type. Continuous operation to 300°F.</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

OPTIONAL CONSTRUCTION

<p>Brass Connection Fittings. <input type="checkbox"/> 3/8" brass compression type. <input type="checkbox"/> Barbed fitting for 1/4" O.D. tubing. <input type="checkbox"/> Barbed fitting for 3/8" O.D. tubing.</p>	<p>Bolt Holes. Size _____ Qty. _____</p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------

Size	4"	5"	6"	7"	8"
O.D.	4.00	5.00	6.00	7.00	8.00
I.D.	3.90	4.90	5.88	6.87	7.87

DIMENSIONAL SPECIFICATIONS

