

# VELTRON DPT 2500

## ULTRA-LOW DIFFERENTIAL PRESSURE AND FLOW TRANSMITTER

<b>STANDARD CONSTRUCTION</b>	Ultra-low span transmitter. 1/8" FPT, brass signal connection fittings. Manual 3-way zeroing valve. NEMA 12 steel enclosure with quick release latch, conduit port, and internal wiring terminals.					
<b>OPTIONS</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 25%; vertical-align: top;"> <b>Square Root.</b>  <input type="checkbox"/> Off (std)  <input type="checkbox"/> On                 </td> <td style="width: 25%; vertical-align: top;"> <input type="checkbox"/> <b>Bi-Polar</b> </td> <td style="width: 25%; vertical-align: top;"> <b>Display.</b>  <input type="checkbox"/> 3½ digit LCD                 </td> <td style="width: 25%; vertical-align: top;"> <b>Connection Fittings.</b>  <input type="checkbox"/> 1/4" brass compression type  <input type="checkbox"/> 3/8" brass compression type  <input type="checkbox"/> Brass barbed for 1/4" OD tubing  <input type="checkbox"/> Brass barbed for 3/8" OD tubing                 </td> <td style="width: 25%; vertical-align: top;"> <b>Certification.</b>  <input type="checkbox"/> Standard  <input type="checkbox"/> NIST Traceable                 </td> </tr> </table>	<b>Square Root.</b> <input type="checkbox"/> Off (std) <input type="checkbox"/> On	<input type="checkbox"/> <b>Bi-Polar</b>	<b>Display.</b> <input type="checkbox"/> 3½ digit LCD	<b>Connection Fittings.</b> <input type="checkbox"/> 1/4" brass compression type <input type="checkbox"/> 3/8" brass compression type <input type="checkbox"/> Brass barbed for 1/4" OD tubing <input type="checkbox"/> Brass barbed for 3/8" OD tubing	<b>Certification.</b> <input type="checkbox"/> Standard <input type="checkbox"/> NIST Traceable
<b>Square Root.</b> <input type="checkbox"/> Off (std) <input type="checkbox"/> On	<input type="checkbox"/> <b>Bi-Polar</b>	<b>Display.</b> <input type="checkbox"/> 3½ digit LCD	<b>Connection Fittings.</b> <input type="checkbox"/> 1/4" brass compression type <input type="checkbox"/> 3/8" brass compression type <input type="checkbox"/> Brass barbed for 1/4" OD tubing <input type="checkbox"/> Brass barbed for 3/8" OD tubing	<b>Certification.</b> <input type="checkbox"/> Standard <input type="checkbox"/> NIST Traceable		
<b>PERFORMANCE SPECIFICATIONS</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> <b>Accuracy.</b> ±0.5% of Natural Full Span, including non-linearity, hysteresis, deadband, and non-repeatability.   <b>Stability.</b> ±0.5% of Natural Full Span for six months.   <b>Power Supply Effect.</b> ±0.005% of Full Span/VDC.                 </td> <td style="width: 50%; vertical-align: top;"> <b>Temperature Effect.</b> Zero. 0.015% of Natural Full Span/°F.                      Span. 0.015% of Natural Full Span/°F.   <b>Mounting Position Effect.</b> Zero shift only, no span shift.                      Corrected through transmitter zeroing.                 </td> </tr> </table>	<b>Accuracy.</b> ±0.5% of Natural Full Span, including non-linearity, hysteresis, deadband, and non-repeatability.  <b>Stability.</b> ±0.5% of Natural Full Span for six months.  <b>Power Supply Effect.</b> ±0.005% of Full Span/VDC.	<b>Temperature Effect.</b> Zero. 0.015% of Natural Full Span/°F. Span. 0.015% of Natural Full Span/°F.  <b>Mounting Position Effect.</b> Zero shift only, no span shift. Corrected through transmitter zeroing.			
<b>Accuracy.</b> ±0.5% of Natural Full Span, including non-linearity, hysteresis, deadband, and non-repeatability.  <b>Stability.</b> ±0.5% of Natural Full Span for six months.  <b>Power Supply Effect.</b> ±0.005% of Full Span/VDC.	<b>Temperature Effect.</b> Zero. 0.015% of Natural Full Span/°F. Span. 0.015% of Natural Full Span/°F.  <b>Mounting Position Effect.</b> Zero shift only, no span shift. Corrected through transmitter zeroing.					
<b>FUNCTIONAL SPECIFICATIONS</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> <b>Outputs.</b> 4-20mA DC.   <b>Power Supply.</b> 14-40VDC (0 to 1200 ohms). Two-wire configuration.   <b>Damping.</b> Time constant adjustable via jumper selection.   <b>Overpressure/Static Pressure Limit.</b> 25 psig.   <b>Zero Elevation/Suppression.</b>                      Maximum zero elevation: 100% of Natural Full Span.                      Maximum zero suppression: 50% of Natural Full Span.                 </td> <td style="width: 50%; vertical-align: top;"> <b>Circuit Protection.</b> Power input is reverse polarity short circuit proof.   <b>Humidity Limits.</b> 0-95% RH (non-condensing).   <b>Temperature Limits.</b> -20°F to 180°F Storage.                      +40°F to 140°F Operating.   <b>Load Limitations.</b> 50 ohms/volt.                      0 ohms at 14VDC.                      1300 ohms at 40VDC.                 </td> </tr> </table>	<b>Outputs.</b> 4-20mA DC.  <b>Power Supply.</b> 14-40VDC (0 to 1200 ohms). Two-wire configuration.  <b>Damping.</b> Time constant adjustable via jumper selection.  <b>Overpressure/Static Pressure Limit.</b> 25 psig.  <b>Zero Elevation/Suppression.</b> Maximum zero elevation: 100% of Natural Full Span. Maximum zero suppression: 50% of Natural Full Span.	<b>Circuit Protection.</b> Power input is reverse polarity short circuit proof.  <b>Humidity Limits.</b> 0-95% RH (non-condensing).  <b>Temperature Limits.</b> -20°F to 180°F Storage. +40°F to 140°F Operating.  <b>Load Limitations.</b> 50 ohms/volt. 0 ohms at 14VDC. 1300 ohms at 40VDC.			
<b>Outputs.</b> 4-20mA DC.  <b>Power Supply.</b> 14-40VDC (0 to 1200 ohms). Two-wire configuration.  <b>Damping.</b> Time constant adjustable via jumper selection.  <b>Overpressure/Static Pressure Limit.</b> 25 psig.  <b>Zero Elevation/Suppression.</b> Maximum zero elevation: 100% of Natural Full Span. Maximum zero suppression: 50% of Natural Full Span.	<b>Circuit Protection.</b> Power input is reverse polarity short circuit proof.  <b>Humidity Limits.</b> 0-95% RH (non-condensing).  <b>Temperature Limits.</b> -20°F to 180°F Storage. +40°F to 140°F Operating.  <b>Load Limitations.</b> 50 ohms/volt. 0 ohms at 14VDC. 1300 ohms at 40VDC.					
<b>DIMENSIONAL SPECIFICATIONS</b>	<p>The drawing shows a side view of the transmitter with the following dimensions: overall width 7.12, distance between ports 6.44, distance from left edge to high port 2.13, and distance from high port to low port 2.13. The front panel has a height of 6.44 and a width of 4.12. Mounting centers are 6.50 apart. A slot at the bottom is .22 x .28. A note indicates the zeroing valve is inside. Labels include 'HIGH PORT', 'LOW PORT', 'LATCH COVER', 'OPTIONAL DISPLAY', and 'SLOT .22 x .28'. A separate detail shows the output terminals (+ and -) located inside the enclosure, with a width of 4.31 and a terminal offset of 1.80.</p>					

