

AIRFLOW METER TYPE S - STATIONARY

STANDARD CONSTRUCTION

Type.	Stationary, wall mounted
Gauge.	Diaphragm activated, differential pressure
Enclosure.	Aluminum, NEMA 1
Signal Fittings.	1/4" brass compression
Display.	Dual scale

PERFORMANCE SPECIFICATIONS

Accuracy.	Rated at 70°F, ±2.0% for 1.0" to 6.0" w.c. range; ±3.0% for 0.50" w.c. range; ±4.0% for 0.25" w.c. range
Overpressurization Limit.	-20" Hg to 15 psig on either side of diaphragm.
Temperature Limit.	20°F to 140°F Operating

OPTIONS

- | | | | |
|---|--------------------------------------|--|---|
| <input type="checkbox"/> Identification Tag | <input type="checkbox"/> Signal Flag | Signal Fittings | Scale Options |
| | | <input type="checkbox"/> 3/8" brass compression type | <input type="checkbox"/> Air volume and velocity |
| | | <input type="checkbox"/> Barbed fitting for 3/8" O.D. tubing | <input type="checkbox"/> Velocity and velocity pressure |
| | | | <input type="checkbox"/> Static pressure |
| | | | <input type="checkbox"/> Resistance to airflow |

DIMENSIONAL SPECIFICATIONS

