

TEMPERATURE PROBE

MULTI-POINT

SELF-SUPPORTED

STANDARD CONSTRUCTION			
Temperature Element.	Thermocouple, with three sensors.		
Temperature Element Sheathing.	½" diameter, 316 stainless steel.		
Temperature J-Box.	NEMA 4, cast aluminum.		
Temperature Transmitter.	2-wire, 4-20mA non-isolated, linearized output. (24 to 40VDC loop power required.)		
Mounting Plate.	6" x 6", 316 stainless steel.		
Support Tube.	316 stainless steel.		
PERFORMANCE SPECIFICATIONS			
Thermocouple Accuracy.	Per ANSI Circular MC 96.1 - 1982.		
Temperature Transmitter Range.	_____ to _____.		
OPTIONS			
Thermocouple Type.	Standoff.	High Temperature Gasket.	Transmitter Type.
<input type="checkbox"/> K <input type="checkbox"/> E <input type="checkbox"/> J	<input type="checkbox"/> 9" (standard) <input type="checkbox"/> Other _____	<input type="checkbox"/> Silicone, 200°F to 400°F <input type="checkbox"/> Fiber, 400°F to 900°F	<input type="checkbox"/> Optically Isolated
DIMENSIONAL SPECIFICATIONS			