

SUBMITTAL SHEET

CAMM

COMBUSTION AIRFLOW MANAGEMENT MODULE

OPTIONS	Special Functions <input type="checkbox"/> Summed Flow <input type="checkbox"/> Differential Flow	Power <input type="checkbox"/> 24VAC <input type="checkbox"/> 20-40VDC <input type="checkbox"/> 120VAC (via external transformer)	Certification <input type="checkbox"/> Standard <input type="checkbox"/> NIST Traceable	Network <input type="checkbox"/> None (std) <input type="checkbox"/> Modbus TCP/IP over Ethernet <input type="checkbox"/> LonWorks
----------------	----------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------

PERFORMANCE SPECIFICATIONS																									
<p>Accuracy. ±0.1% of Natural Span, including non-linearity, hysteresis, and non-repeatability.</p> <p>Stability. ±0.5% of Natural Span for six months.</p> <p>Temperature Effect Zero. None; corrected by AUTO-zero. Span. 0.015% of Full Span/°F.</p> <p>Mounting Position Effect. None; corrected by AUTO-zero.</p>	<p>Transducer Response Time. 0.5 second to reach 98% of a step change.</p> <p>Power Consumption.</p> <table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">Standard</th> <th colspan="2">w/AUTO-purge</th> </tr> <tr> <th>In Rush</th> <th>Hold</th> <th>In Rush</th> <th>Hold</th> </tr> </thead> <tbody> <tr> <td>24VAC</td> <td>14.4VA</td> <td>14VA</td> <td>45.6VA</td> <td>33.68VA</td> </tr> <tr> <td>24VDC</td> <td>9.6W</td> <td>9.0W</td> <td>19.92W</td> <td>19.32W</td> </tr> <tr> <td>120VAC</td> <td>19.2VA</td> <td>18.67VA</td> <td>60.8VA</td> <td>44.91VA</td> </tr> </tbody> </table>		Standard		w/AUTO-purge		In Rush	Hold	In Rush	Hold	24VAC	14.4VA	14VA	45.6VA	33.68VA	24VDC	9.6W	9.0W	19.92W	19.32W	120VAC	19.2VA	18.67VA	60.8VA	44.91VA
	Standard		w/AUTO-purge																						
	In Rush	Hold	In Rush	Hold																					
24VAC	14.4VA	14VA	45.6VA	33.68VA																					
24VDC	9.6W	9.0W	19.92W	19.32W																					
120VAC	19.2VA	18.67VA	60.8VA	44.91VA																					

FUNCTIONAL SPECIFICATIONS	
<p>Digital Outputs. Two Form 'C' contacts and dual Form 'A' dry contacts rated for 3A at 24VAC/DC used for AUTO-purge activation (SV₁ and SV₂) and acknowledgment.</p> <p>Digital Inputs. External dry contact closure for AUTO-purge external start and purge interrupt commands.</p> <p>Analog Outputs. Four outputs for flow, temperature, absolute pressure, and differential pressure or special function individually configurable via jumper for 0-5VDC, 0-10VDC, or 4-20mADC.</p> <p>Analog Inputs. Dual inputs are field configurable via jumper for 0-5VDC, 0-10VDC, or 4-20mADC. One is reserved for temperature input; the other for use with optional special function.</p> <p>AUTO-purge Management. AUTO-purge cycle is initiated via an external dry contact input, or via an internal timer with field selectable frequencies of 1 to 24 hours, in 1 hour increments. A Form 'A' contact controls the AUTO-purge System; a second dry contact provides remote purge activation & acknowledgment.</p> <p>Power Supply. Standard 24VAC (20-28VAC) or 24VDC (20-40VDC), with automatic selection. Optional 120VAC (100-132 VAC) via external UL listed transformer.</p> <p>Low Pass Filtration. Response time to reach 98% of a step change is adjustable from 2.0 to 30.0 seconds.</p>	<p>Automatic Zeroing. Accuracy. Within 0.1% of calibrated span. Frequency. Every 1 to 24 hours selectable on 1 hour intervals.</p> <p>Overpressure and Static Pressure Limit. 25 psig.</p> <p>Circuit Protection. Power input is fused and reverse polarity protected.</p> <p>Span and Zero Adjustment. Digital, via internally located push-buttons.</p> <p>Displays. Standard 5 line x 20 character backlit graphical LCD provides five lines of data display. LED's indicate CPU activated, AUTO-zero in progress, and AUTO-purge in progress.</p> <p>Temperature Compensation Selection. Push-button selection of linearized or nonlinear input. Choice of thermocouple (Type E, K, J, and T) or 100 ohm platinum RTD temperature sensor type.</p> <p>Pressure Compensation. Absolute pressure (atmosphere or duct static), up to 60"Hg.</p> <p>Humidity Limits. 0-95% RH, non-condensing.</p> <p>Temperature Limits. -20°F to 180°F Storage. +40°F to 140°F Operating.</p>

