

VOLU-probe / VS – Stainless Steel – Industrial

Circular Configuration

90° Flange




STANDARD CONSTRUCTION

Casing. 14 gauge, Type 316 stainless steel, continuously welded.
Flanges. Up to 24" diameter: 1" flange, 14 ga., Type 316 stainless steel, fusion welded to casing.
 25" - 44" diameter: 1-1/2" flange, 14 ga., Type 316 stainless steel, fusion welded to casing.
 45" plus diameter: 3/16" x 2", Type 316 stainless steel barstock welded to casing.
Connection Fittings. 1/2" FPT, stainless steel.
Total and Static Pressure Probes. Type 316 stainless steel. Neoprene gaskets (0 to 200°F).
Operating Temperature. Continuous to 900°F.

OPTIONS

- External Manifolding
 - 1/4" tubing and compression type fittings.
 - 1/2" tubing and compression type fittings.
- Extended Flanges.
 - Size _____
 - Bolt Holes (per flange)
 - Size _____
 - Qty _____
 - Bolt Circle Dia. _____
- High Temperature Probe Gaskets
 - Silicone; 200°F to 400°F
 - Ceramic Fiber; 400°F to 900°F

DIMENSIONAL SPECIFICATIONS



I.D.	NUMBER OF PROBES	A	B
8" THRU 18"	1	6.00	—
>18" THRU 24"	2	6.00	90°
>24" THRU 72"	2	8.00	90°
>72"	3	10.00	60°

